

MH-380 (parallel 2-needle) MH-382 (tandem 2-needle)

High-speed, Flat-bed, 2-needle Double Chainstitch Machine



MH-380 · MH-382

Various attachments allow the machine to adapt to many different processes.

Many different attachments have been developed for the machine. This means that the JUKI MH Series sewing machine can adapt to many kinds of processes and specifications including hemming, welting and decorative stitching. Accurate stitching performance and durable finished seams are particularly necessary in the chainstitching process. JUKI ensures high-quality sewing with a higher degree of consistency with its unique looper mechanism and consistent condensation stitching mechanism. Furthermore, highly efficient operation is achieved by using a chain-off thread cutting device.



The machine ensures outstanding reliability and durability.

It comes with JUKI's unique inclined crank type looper mechanism. This gives the machine outstanding durability. You can use the sewing machine for a long time without ever worrying about looper failure.

Stitch length can be adjusted with ease.

The machine incorporates a stitch dial for adjusting the stitch length. For lockstitch machines, which are the most popular type of sewing machines, the stitch length is also adjusted using a stitch dial. This means you can adjust the stitch length as desired without difficulty.

The machine is capable of performing consistent condensation stitching, ensuring finished seams of higher quality.

You can easily set the machine to perform condensation stitching by operating the lever. Condensation stitches that prevent the thread from fraying can be consistently sewn.

Many different kinds of attachments contribute to enhanced production efficiency.

Attachments (optional) have been prepared for many different applications, including sewing sides of jeans, slacks and skirts, hemming pockets, making decorative stitches on tape for sportswear. Furthermore, a chain-off thread cutter (AT-8, optional) that helps enhance production efficiency is also available.

■ DEVICES AND ATTACHMENTS

●Chain-off thread cutter Applicable machines: MH-380, MH-382 Class of work: Jeans, Working wear

Applications: Cut a chaining thread bridging two workpieces continuously sewn by chainstitch in the way that a knife blade of the cutter is dropped. Best suited for continuous sewing on pocket openings of jeans or working wear.

AT-8



Guide width mm (in)	Part No.
Tandem 2-needle	40042785
4.0 (5/32)	40042787
4.8 (3/16)	40042788
6.4 (1/4)	40042790
7.9 (5/16)	40042791

Down turn hemmer

Applicable machines: MH-380 Class of work: Jeans, Working pants

Applications: Hem jeans hip pocket mouth, especially suit for sections where high quality straight stitch is

A: Needle gauge

L050

Finished width (mm)	Part No.
14	MAL-0500P0A0
12	MAL-0500M0A0
11	MAL-0500L0A0
10	MAL-0500K0A0

Decorative tape attaching foot

B050

B: Finished width

Applicable machines: MH-380 Class of work: Sportswear, Training wear, Swimsuits,

Applicable machines: MH-380

Uniforms, Boxer pants, Rompers

Applications: Stitch accent line attach tapes Materials: Cotton bias tape, or plain woven tape for some limited process.

Finished width (mm)	Needle gauge mm (in)	Tape width (mm)	Part No.
17	12.7 (1/2)	34	MAB-0500SLA0
15	9.5 (3/8)	30	MAB-0500QKA0
12	7.9 (5/16)	24	MAB-0500MHA0
10	6.4 (1/4)	20	MAB-0500KFA0
8	4.8 (3/16)	16	MAB-0500HDA0
6	4.0 (5/32)	14	MAB-0500GCA0

Decorative tape attaching foot

A: Needle gauge B: Finished width

> Class of work: Ladies' wear, Children' wear, Sportswear, Uniforms

Applications: Attach decorative tapes and reinforcement tapes

B051

Materials: Tape: Synthetic suede cloth tape, decorative tape, plain woven tape. Contact us for special type of tapes.



Finished width (mm)	Needle gauge mm (in)	Part No.
17	12.7 (1/2)	MAB-0510SLA0
15	9.5 (3/8)	MAB-0510QKA0
12	7.9 (5/16)	MAB-0510MHA0
10	6.4 (1/4)	MAB-0510KFA0
9	5.6 (7/32)	MAB-0510JEA0
8	4.8 (3/16)	MAB-0510HDA0

B: Finished width Tape cutter

AT28

A: Needle gauge

WHEN YOU PLACE ORDERS

Switch

	i iiigei siiiiteii	
	Knee switch	В
	*Needle gauges,	1/8,
	5/32, 3/16, 3/8	and
1/2, should be		
specially orderd.		

Code	Needle gauge mm (in)
В	3.2 (1/8")
С	4.0 (5/32")
D	4.8 (3/16")
E	5.6 (7/32")
F	6.4 (1/4")
Н	7.9 (5/16")
K	9.5 (3/8")
L	12.7 (1/2")

■ SPECIFICATIONS

Applicable model: MH-380 (Cannot be use with the thread trimmer type.)

Operating method: Air drive by air switch

Applications : Cutting various tapes related to attaching

reinforcement tape and decorative tape

Cut specifications: Knife width 20mm

Cutting range of the knife 16mm or less

Air pressure : 0.15~0.5 MPa (1.5~5.0kgf/cm²) Lap seam folder (Reverse) Applicable machines: MH-380

Class of work: Jeans, Working pants, Pants, Overalls

Applications: Sew side seams

Attach flat faces of garments.

Materials: Medium heavy-weight materials and heavyweight materials such as denim, drill, etc.



M052

A: Needle gauge
R. Finished width

Finished width (mm)	Needle gauge mm (in)	Part No.
17	12.7 (1/2)	MAM-0520S0A0
14	9.5 (3/8)	MAM-0520P0A0
12	7.9 (5/16)	MAM-0520M0A0
10	6.4 (1/4)	MAM-0520K0A0
10	5.6 (7/32)	MAM-0520K0A0
9	4.8 (3/16)	MAM-0520J0A0

Left feed top stitch folder

Applicable machines: MH-380 Class of work: Jeans, Working pants, Jackets, Skirts Applications: Sew side seams.

M054



A: Needle gauge B: Finished width

Finished width (mm)	Needle gauge mm (in)	Part No.
17	12.7 (1/2)	MAM-0540S0A0
14	9.5 (3/8)	MAM-0540P0A0
12	7.9 (5/16)	MAM-0540M0A0
10	6.4 (1/4)	MAM-0540K0A0
10	5.6 (7/32)	MAM-0540K0A0
9	4.8 (3/16)	MAM-0540J0A0
8	4.0 (5/32)	MAM-0540H0A0

Right feed top stitch folder

Applicable machines: MH-380 Class of work: Jeans, Working pants, Jackets, Skirts Applications: Sew side seams. Attach flat faces of garments.

M055



A: Needle gauge B: Finished width

Finished width (mm)	Needle gauge mm (in)	Part No.
17	12.7 (1/2)	MAM-0550S0A0
14	9.5 (3/8)	MAM-0550P0A0
12	7.9 (5/16)	MAM-0550M0A0
10	6.4 (1/4)	MAM-0550K0A0
10	5.6 (7/32)	MAM-0550K0A0
9	4.8 (3/16)	MAM-0550J0A0
8	4.0 (5/32)	MAM-0550H0A0

Superpose joining guide **Applicable machines: MH-382**

Applications: Used with lockstitch machines or chainstitch machines to sew side seam, and similar runstitch & joining edge of garments with different curve lines



*
e allowance:
20,000,000
. 20mm

Туре	Part No.
Light-weight material	MAH-027000AA
Medium-weight material	MAH-027000AB
Heavy-weight material	MAH-027000AH
Spacer (assy.)	MAH-025020A0

Zipper guide

Applicable machines: MH-380 Class of work: Jeans, Working pants **Applications:** Sew zippers on left files



Materials: Medium-weight materials such as jeans denim, cotton gabardine, drill etc.

Part No.	
MAQ-020000A0	
MAQ-020000A0	

APPLICATIONS

Model	Application				
MH-380 (parallel 2-needle)	Sewing sides of slacksHemming or welting garment partsAttaching lining tape				
MH-382 (tandem 2-needle)	Joining seat of slacks				

TABLE OF EXCHANGING GAUGE SETS

MH-380

Description	iption Throat plate Needle clamp asm.		hroat plate Needle clamp asm. Presser foot asm. (with finger guard) Feed dog		Rear moving needle guard	Right fix needle guard	Left needle guard	
Gauge components		(<u>0 ° ()</u>						
3.2mm (1/8")	B1103-380-B00	B1406-019-BA0	B1509-038-BB0	B1613-380-B00		B2315-380-000	B2312-380-000	
4.0mm (5/32")	B1103-380-C00	B1406-019-CA0	B1509-038-CB0	D1013-360-D00	B2311-380-B00			
4.8mm (3/16")	B1103-380-D00	B1406-019-DA0	B1509-038-DB0	B1613-380-D00				
5.6mm (7/32")	B1103-380-E00	B1406-019-EA0	B1509-038-EB0	B1613-380-F00	B2311-380-E00			
6.4mm (1/4")	mm (1/4") B1103-380-F00 B1406-019-FA0		B1509-038-FB0	D1013-360-F00	B2311-360-E00	B2313-360-000	B2312-360-000	
7.9mm (5/16")	B1103-380-H00	B1406-038-HA0	B1509-038-HB0	B1613-380-H00 B2311-380-H00				
9.5mm (3/8")	9.5mm (3/8") B1103-380-K00 B1406-038-KA		B1509-038-KB0	B1613-380-K00	B2311-360-F100			
12.7mm (1/2")	m (1/2") B1103-380-L00 B1406-038-LA0 B1509-038-LBB		B1509-038-LBB	B1613-380-L00	B2311-380-L00			
MH-382								
_	B1103-382-000	B1406-019-BA0	B1524-382-0B0	B1613-382-000	B2311-382-000	B2312-:	382-000	

MH-380

MI1-300										
Description	Right looper	Left looper	Bed slide asm.	Bed slide asm.	Folder					
	Rigiit loopei	Left looper	bed silde asili.	bed silde asili.	M	МН	н			
Gauge components			S							
3.2mm (1/8")			B1104-380-AA0	B1108-380-BA0 B1108-380-HA0	B9126-038-BAA	B9126-038-BAB	B9126-038-BAC			
4.0mm (5/32")		B2031-380-000			B9126-038-CAA	B9126-038-CAB	B9126-038-CAC			
4.8mm (3/16")					B9126-038-DAA	B9126-038-DAB	B9126-038-DAC			
5.6mm (7/32")	B2030-380-000				B9126-038-EAA	B9126-038-EAB	B9126-038-EAC			
6.4mm (1/4")					B9126-038-FAA	B9126-038-FAB	B9126-038-FAC			
7.9mm (5/16")					B9126-038-HAA	B9126-038-HAB	B9126-038-HAC			
9.5mm (3/8")					_	_	_			
12.7mm (1/2")				B1108-380-LA0	_	-	_			
MH-382										
_	B2030-380-000	B2031-380-000	B1104-380-AA0	B1108-380-BA0	_	_	_			

■ SPECIFICATIONS

Madal	MH-380	MH-382				
Model name	Parallel 2-needle	Tandem 2-needle				
Max. sewing speed	6,000rpm					
Max. stitch length	4m	nm				
Lift of the presser foot	By hand: 5.5mm,	By knee: 10mm				
Needle bar stroke	30r	nm				
Needle (at the time of delivery)	TV×7 (#14) #9~#21					
Thread take-up	Needle bar thread take-up					
Stitch length adjustment	By stitch dial (lockstitch)					
Condensation stitches	By lever for condensation stitching					
Looper system	Rocking type looper					
Looper stroke	22.6	mm				
Elliptical motion	2.4~3.7mm					
Lubrication	Automatic					
Lubricating oil	JUKI New Defrix Oil No.1 (equivalent to ISO VG7)					
Needle cooler	Optional					



1) Size code

3.2mm (1/8") = B	
4.0mm (5/32") = C	
4.8mm (3/16") = D	
5.6mm (7/32") = E	
6.4mm (1/4") = F	
7.9mm (5/16") = H	
9.5mm (3/8") = K	
12.7mm (1/2") = L	

2) Folder code

М	(for light weight materials) = A
MH	f (for medium heavy weight materials) = B
Н	(for heavy weight materials) = C

WHEN YOU PLACE ORDERS

Please note when placing orders, that the model name should be written as follows:

MH380 U MH382U										J		
		Code	В	С	D	E	F	G	Н	K	L	N
	Needle gauge	mm	3.2	4.0	4.8	5.6	6.4	7.1	7.9	9.5	12.7	19.1
-		inch	1/8	5/32	3/16	7/32	1/4	9/32	5/16	3/8	1/2	3/4

• To order, please contact your nearest JUKI distributor.



JUKI CORPORATION MARKETING & SALES H.Q.

® 8-2-1, KOKURYO-CHO, CHOFU-SHI, TOKYO 182-8655, JAPAN

PHONE: (81) 3-3480-2357, 2358 FAX: (81) 3-3430-4909

http://www.juki.com * Specifications and appearance are subject to change without prior notice for improvement.

- * Specifications and appearance are subject to change without prior notice to improve Read the instruction manual before putting the machine into service to ensure safety.
 * This catalogue prints with environment-friendly soy ink on recycle paper.